



Product Parameters (产品描述)

产品编号 | Part Number: KB-H15-xxF-5050
出光角度 | Beam Angle: 25/30/40/50/25*45°
产品材料 | Material: PMMA
工作温度 | Work Temp: <85°C

安装方式 | Fastening: Tape/Glue
支架颜色 | Holder Color: White
透光率 | Transmittance: 93%
匹配LED | Match Led: SMD5050

Part Number	Lens Surface	Dimension	Beam Angle
KB-H15-20PF-5050	珠面/beads	Φ14.85*H6.3mm	~25°
KB-H15-30PF-5050	珠面/beads	Φ14.85*H6.3mm	~30°
KB-H15-45PF-5050	珠面/beads	Φ14.85*H6.3mm	~40°
KB-H15-60PF-5050	珠面/beads	Φ14.85*H6.3mm	~50°
KB-H15-2545F-5050	条纹面/strip	Φ14.85*H6.3mm	~25*45°

Direction for Use

(透镜 | LENS)


- 1, Please use some soft paper or pure water to clean lens (reflector)
- 2, Don't use any industrial solvent to clean lens surface , such as alcohol
- 3, Storage environment : Temperature 0~40°C , Humidity 30%~95%
- 4, This kind of lens can make the lighting more concentrated, and it's made from transparent material , so please do not open the packages until you use them, in case of the dust and other pollutions.

(双面胶 | TAPE)


- 1, Ensure the assembled pcb is straight, so the tape can be fully sticked to the surface.
- 2, Ensure the assembled pcb is clean and dry, any dirt or unknown chemicals may affect the tape viscous force.
- 3, Stress lens 1~5 seconds after assembly to ensure 100% bond.
- 4, Check lens one by one after assembly to ensure all lens are sticked properly, if lens was not sticked to led perfectly, lens will be a bit suspended, picked it off to stick again or replace with a new tape.

Light Distribution Curve (配光曲线图):


Part Number: KB-H15-20PF-5050



Part Number: KB-H15-30PF-5050




Part Number: KB-H15-45PF-5050




Light Distribution Curve (配光曲线图):


Part Number: KB-H15-60PF-5050





Part Number: KB-H15-2545F-5050



Mechanical Characteristics (产品尺寸):



Product Package (产品包装):

Inner Box (内盒)	Outer Carton (外箱)
	
<p>49pcs/layer 17 layers/box Gross weight: 733g/box Box dimension: 12.2*12.3*13.4cm</p>	<p>20boxes/carton 16,660pcs/carton Gross weight: 15.5kg/CTN Carton Dimension: 64*29*26cm</p>