



### Product Parameters (产品描述)

产品编号 | Part No.: KB-H22-xxF-Tape  
出光角度 | Angle: 8/10/15/30/45/60/Oval  
产品材料 | Material: PMMA  
工作温度 | Work Temp: <85°C

安装方式 | Fastening: Pins+Glue  
支架颜色 | Holder Color: N/A  
透光率 | Transmittance: 93%  
匹配LED | Match Led: Dome/Flat 3030|3535

Part Number	Lens Surface	Dimension	Beam Angle
KB-H22-8MFZ-3030	沙面/matt	Φ22.7*H12mm	~8°
KB-H22-10PFZ-3030	珠面/beads	Φ22.7*H12mm	~10°
KB-H22-15PFZ-3030	珠面/beads	Φ22.7*H12mm	~15°
KB-H22-30PFZ-3030	珠面/beads	Φ22.7*H12mm	~30°
KB-H22-45PFZ-3030	珠面/beads	Φ22.7*H12mm	~45°
KB-H22-60PFZ-3030	珠面/beads	Φ22.7*H12mm	~60°
KB-H22-1020FZ-3030	条纹面/strip	Φ22.7*H12mm	~10*20°
KB-H22-1525FZ-3030	条纹面/strip	Φ22.7*H12mm	~15*25°
KB-H22-1535FZ-3030	条纹面/strip	Φ22.7*H12mm	~15*35°
KB-H22-1560FZ-3030	条纹面/strip	Φ22.7*H12mm	~15*60°

### Direction for Use

#### (透镜 | LENS)

- 1, Please use some soft paper or pure water to clean lens ( reflector)
- 2, Don't use any industrial solvent to clean lens surface , such as alcohol
- 3, Storage environment : Temperature 0~40°C , Humidity 30%~95%
- 4, This kind of lens can make the lighting more concentrated, and it's made from transparent material , so please do not open the packages until you use them, in case of the dust and other pollutions.

Mechanical Characteristics (产品尺寸):

