



Product Parameters (产品描述)

产品编号 | Part Number: KB-LN20-xx

出光角度 | Beam Angle: 40|60|90|150|ASY|Double ASY

产品材料 | Material: PMMA

工作温度 | Work Temp: <85℃

安装方式 | Fastening: Plug-in

防水圈 | Silica seal : N/A

透光率 | Transmittance: 85~93%

匹配LED | Match Led: SMD3030/2835/3535

Part Number	Lens Surface	Dimension	Beam Angle
KB-LN20-40	雾面/matt	W19.5*H8MM	~40°
KB-LN20-60	雾面/matt	W19.5*H8MM	~60°
KB-LN20-90	雾面/matt	W19.5*H8MM	~90°
KB-LN20-150	雾面/matt	W19.5*H5.5MM	~150°
KB-LN20-AS	雾面/matt	W19.5*H7.8MM	~Asymmetric
KB-LN20-AS-N	雾面/matt	W19.5*H5.5MM	~Asymmetric
KB-LN20-DAS	雾面/matt	W19.5*H7.8MM	~Double Asymmetric

Direction for Use

(透镜 | LENS)

- 1, Please use some soft paper or pure water to clean lens (reflector)
- 2, Don't use any industrial solvent to clean lens surface , such as alcohol
- 3, Storage environment : Temperature 0~40℃ , Humidity 30%~95%
- 4, This kind of lens can make the lighting more concentrated, and it's made from transparent material , so please do not open the packages until you use them, in case of the dust and other pollutions.



